



## Spiraal kokers

### OMSCHRIJVING

**GALVA** Kanaal volgens EN 1506 en EN 24145

Materiaal: Gegalvaniseerd staal

Ød 80 tot 1250 mm

**INOX** Kanaal volgens EN 1506 en EN 24145

Materiaal: Inox

Ød 80 tot 1250 mm



| Ød<br>DN | Vrij doorsnede<br>per run. m (m <sup>2</sup> ) | Gewicht<br>(kg/m) |
|----------|------------------------------------------------|-------------------|
| 80       | 0.005                                          | 1.1               |
| 100      | 0.008                                          | 1.7               |
| 125      | 0.012                                          | 2.1               |
| 140      | 0.015                                          | 2.4               |
| 150      | 0.018                                          | 2.5               |
| 160      | 0.020                                          | 2.7               |
| 180      | 0.025                                          | 3.1               |
| 200      | 0.031                                          | 3.4               |
| 224      | 0.039                                          | 3.8               |
| 250      | 0.049                                          | 4.2               |
| 280      | 0.062                                          | 4.7               |
| 300      | 0.071                                          | 6.8               |
| 315      | 0.078                                          | 7.1               |
| 355      | 0.099                                          | 8.0               |
| 400      | 0.126                                          | 9.0               |
| 450      | 0.159                                          | 10.1              |
| 500      | 0.196                                          | 11.3              |
| 560      | 0.246                                          | 12.6              |
| 600      | 0.283                                          | 13.5              |
| 630      | 0.312                                          | 17.7              |
| 710      | 0.396                                          | 20.0              |
| 800      | 0.503                                          | 22.5              |
| 900      | 0.636                                          | 25.3              |
| 1000     | 0.785                                          | 34.4              |
| 1120     | 0.985                                          | 38.6              |
| 1250     | 1.227                                          | 43.0              |